

## PANDOC COMMAND LINE ARGUMENTS & OPTIONS IN DEFAULTS FILES

Notes:

“(n/a)”

defaults version does not exist and would not make sense

“(dep.)”

deprecated option – should a defaults version exist?

command line	defaults file
[FILE]	input-file: FILE
[FILES]	input-files: - FILE (for each file)
--from=FORMAT[EXTENSIONS]	reader: FORMAT[EXTENSIONS]
--to=FORMAT[EXTENSIONS]	writer: FORMAT[EXTENSIONS]
--output=FILE	output-file: FILE
--output=-	output-file:
--data-dir=DIRECTORY	data-dir: DIRECTORY
--metadata=KEY[:VALUE]	metadata: KEY: VALUE true
--metadata-file=FILE	metadata-files: - FILE
--defaults=FILE	(n/a)
--file-scope	file-scope: true
--standalone	standalone: true
--template=FILE	template: FILE
--variable=KEY[:VALUE]	variables: KEY: VALUE true
--wrap=auto none preserve	wrap: auto none preserve
--ascii	ascii: true
--toc	toc: true (or table-of-contents:)
--toc-depth=NUMBER	toc-depth: NUMBER
--number-sections	number-sections: true
--number-offset=NUMBERS	number-offset: NUMBERS (as list)
--top-level-division=section chapter part	top-level-division: section chapter part

command line	defaults file
<code>--extract-media=PATH</code>	<code>extract-media: PATH</code>
<code>--resource-path=SEARCHPATH</code>	<code>resource-path: SEARCHPATH (as list)</code>
<code>--include-in-header=FILE</code>	<code>include-in-header:</code> <code>- FILE</code>
<code>--include-before-body=FILE</code>	<code>include-before-body: FILEs</code> <code>- FILE</code>
<code>--include-after-body=FILE</code>	<code>include-after-body: FILEs</code> <code>- FILE</code>
<code>--no-highlight</code>	<code>highlight-style: null</code>
<code>--highlight-style=STYLE FILE</code>	<code>highlight-style: STYLE FILE</code>
<code>--syntax-definition=FILE</code>	<code>syntax-definitions:</code> <code>- FILE</code>
<code>--dpi=NUMBER</code>	<code>dpi: NUMBER</code>
<code>--eol=crlf lf native</code>	<code>eol: crlf lf native</code>
<code>--columns=NUMBER</code>	<code>columns: NUMBER</code>
<code>--preserve-tabs</code>	<code>preserve-tabs: true</code>
<code>--tab-stop=NUMBER</code>	<code>tab-stop: NUMBER</code>
<code>--pdf-engine=PROGRAM</code>	<code>pdf-engine: PROGRAM</code>
<code>--pdf-engine-opt=STRING</code>	<code>pdf-engine-opts:</code> <code>- STRING</code>
<code>--reference-doc=FILE</code>	<code>reference-doc: FILE</code>
<code>--self-contained</code>	<code>self-contained: true</code>
<code>--request-header=NAME:VALUE</code>	<code>request-headers:</code> <code>- ["NAME", "VALUE"]</code>
<code>--abbreviations=FILE</code>	<code>abbreviations: FILE</code>
<code>--indented-code-classes=STRING</code>	<code>indented-code-classes:</code> <code>- STRING</code>
<code>--default-image-extension=EXTENSION</code>	<code>default-image-extension: EXTENSION</code>
<code>--filter=PROGRAM</code>	<code>filters:</code> <code>- PROGRAM</code>
<code>--lua-filter=SCRIPTPATH</code>	<code>filters:</code> <code>- path: SCRIPTPATH</code> <code>type: lua</code>

command line	defaults file
<code>--filter pandoc-citeproc</code>	<code>cite-method: citeproc</code>
<code>--shift-heading-level-by=NUMBER</code>	<code>shift-heading-level-by: NUMBER</code>
<code>--base-header-level=NUMBER (dep.)</code>	<code>shift-heading-level-by: N-1</code>
<code>--strip-empty-paragraphs (dep.)</code>	<code>strip-empty-paragraphs: true</code>
<code>--track-changes=accept reject all</code>	<code>track-changes: accept reject all</code>
<code>--strip-comments</code>	<code>strip-comments: true</code>
<code>--reference-links</code>	<code>reference-links: true</code>
<code>--reference-location=block section document</code>	<code>reference-location: block section document</code>
<code>--atx-headers</code>	<code>atx-headers: true</code>
<code>--listings</code>	<code>listings: true</code>
<code>--incremental</code>	<code>incremental: true</code>
<code>--slide-level=NUMBER</code>	<code>slide-level: NUMBER</code>
<code>--section-divs</code>	<code>section-divs: true</code>
<code>--html-q-tags</code>	<code>html-q-tags: true</code>
<code>--email-obfuscation=none javascript references</code>	<code>email-obfuscation: none javascript references</code>
<code>--id-prefix=STRING</code>	<code>identifier-prefix: STRING</code>
<code>--title-prefix=STRING</code>	<code>title-prefix: STRING</code>
<code>--css=URL</code>	<code>css:</code> <code>  - URL</code>
<code>--epub-subdirectory=DIRNAME</code>	<code>epub-subdirectory: DIRNAME</code>
<code>--epub-cover-image=FILE</code>	<code>epub-cover-image: FILE</code>
<code>--epub-metadata=FILE</code>	<code>epub-metadata: FILE</code>
<code>--epub-embed-font=FILE</code>	<code>epub-fonts:</code> <code>  - FILE</code>
<code>--epub-chapter-level=NUMBER</code>	<code>epub-chapter-level: NUMBER</code>
<code>--ipynb-output=all none best</code>	<code>ipynb-output: all none best</code>
<code>--bibliography=FILE</code>	<code>metadata: (implies cite-method: citeproc)</code> <code>  bibliography: FILE</code>
<code>--csl=FILE</code>	<code>metadata:</code> <code>  csl: FILE</code>
<code>--citation-abbreviations=FILE</code>	<code>metadata:</code> <code>  citation-abbreviations: FILE</code>
<code>--natbib</code>	<code>cite-method: natbib</code>

---

command line	defaults file
<code>--biblatex</code>	<code>cite-method: biblatex</code>
<code>--mathml</code>	<code>html-math-method: method: mathml</code>
<code>--webtex[=URL]</code>	<code>html-math-method: method: webtex [url: URL]</code>
<code>--mathjax[=URL]</code>	<code>html-math-method: method: mathjax [url: URL]</code>
<code>--katex[=URL]</code>	<code>html-math-method: method: katex [url: URL]</code>
<code>--gladtex[=URL]</code>	<code>html-math-method: method: gladtex [url: URL]</code>
<code>--trace</code>	<code>trace: true</code>
<code>--dump-args</code>	<code>dump-args: true</code>
<code>--ignore-args</code>	<code>ignore-args: true</code>
<code>--verbose</code>	<code>verbosity: INFO</code>
<code>--quiet</code>	<code>verbosity: ERROR</code>
<code>--fail-if-warnings</code>	<code>fail-if-warnings: true</code>
<code>--log=FILE</code>	<code>log-file: FILE</code>
<code>--bash-completion</code>	<code>(n/a)</code>
<code>--list-input-formats</code>	<code>(n/a)</code>
<code>--list-output-formats</code>	<code>(n/a)</code>
<code>--list-extensions[=FORMAT]</code>	<code>(n/a)</code>
<code>--list-highlight-languages</code>	<code>(n/a)</code>
<code>--list-highlight-styles</code>	<code>(n/a)</code>
<code>--print-default-template=FORMAT</code>	<code>(n/a)</code>
<code>--print-default-data-file=FILE</code>	<code>(n/a)</code>
<code>--print-highlight-style=STYLE FILE</code>	<code>(n/a)</code>
<code>--version</code>	<code>(n/a)</code>
<code>--help</code>	<code>(n/a)</code>

---